## 35 Ton Excavator

# T-REX6335S




**Specs**

| General Specifications | |
|---|---|
| Operating Weight | 34800kg |
| Bucket Capacity | 1.9m³ |
| Bucket Capacity Range | 1.6~2.0m³ |
| Ground Pressure Ratio | 63.8kPa |
| Slewing Speed | 10.7r/min |
| Maximum Digging Force | 222.6kN |
| Altitude | 2000m |
| Wading Depth | 815mm |
| Engine Model / Drive Motor Model | BFM8-29T2 |
| Engine Power | 215kW |
| Maximum Flow Rate | 2 x 290 + 25.5L |
| Fuel Specification and Filling Amount | 590L |
| Overall Length | 11000mm |
| Overall Width | 3190mm |
| Overall Height | 3450mm |

| | |
|---|---|
| Boom length | 6200mm |
| Wheel Track | 2590mm |
| Arm Length | 3200mm |
| Wheelbase | 4130mm |
| Crawler Wheelbase / Wheelbase | 4130mm |
| Max. Digging Radius | 10650mm |
| Max. Digging Depth | 7220mm |
| Max. Discharge Height | 10045mm |
| Overall Length During Transfer | 11000mm |
| Bucket Width (with Edge Blade) | 1670mm |
| Max. Digging Depth under Length of Bottom Surface 2.5m | 7025mm |
| Max Digging Height | 10045mm |
| Overall Width of Upper Assembly | 2950mm |
| Overall width of Chassis | 3190mm |
| Overall Height to Cab Top | 3150mm |
| Overall Height to Hood Top | 2885mm |
| Ground Clearance of Upper Assembly | 1215mm |
| Overall Length of Crawler | 5070mm |
| Track Shoe Width | 2590mm |
| Min. Ground Clearance | 520mm |